



Fixture	Label	Arrangement	Lenses	LPF	Description	Watts
18	18	0	SINGLE	0.920	WALL MOUNT STANDARD DOME LUMINAIRE - T8/CA/SC/SCENT - 250W MAX (SUGGESTED USE OF 42K CFL LAMP) - WTS NOT SHOWN ON ELEVATIONS	42
19	19	0	SINGLE	0.741	POLE MOUNTED LUMINAIRE - T8/CA/SC/SCENT - 250W MAX (SUGGESTED USE OF 42K CFL LAMP) - WTS NOT SHOWN ON ELEVATIONS	125

Label	CalcType	Units	Avg	Max	Min	Avg/Min	Max/Min
ENTRANCE DRIVE	Illuminance	Fc	2.77	5.7	0.8	3.46	7.13
HANDICAP PARKING AND EXIT	Illuminance	Fc	3.49	8.3	0.7	4.99	11.86
PROPERTY LINE	Illuminance	Fc	0.37	1.0	0.0	N.A.	N.A.
MAIN PARKING	Illuminance	Fc	4.74	9.0	2.1	2.26	4.29

KW / LOCATION PHOTOMETRIC LAYOUT - RLL DESIGN, LP
 LABEL E = .47kw 8-18-08
 LABEL C = .2kw (MAX)